

I. PRODUCT IDENTIFICATION

PRODUCT No's 010 and 050

PRODUCT NAME: JUST-FOR-COPPER (Cold Welding For Rigid Copper Pipes) Issued: 05/12/03

PRODUCT TYPE: (Esther Methacrylate)

FORMULA No. : Does not apply

• COMPANY IDENTIFICATION AND TELEPHONE NUMBER.

Jackson Industries, Inc. , 1 Deer Path, Suite 3, Maynard, MA 01754

Phone Toll Free: 888-704-0015 or 508-932-5205 or 5208

E-mail : info@justforcopper.com Web: www.justforcopper.com

II. COMPOSITION

Ingredients	CAS No.
Dimethacrylate	25852-47-5
Bisphenol A fumarate resin	39382-25-7
CUSMENE HYDROPEROXIDE*	80-15-9
SACCHARIN*	81-07-2
N , N-Dialkyltoluidines	613-48-9
ACRYLIC ACID	79-10-7

III. CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure:	Less than 5mm at 80°F
Vapor Density:	Not available
Solubility in water:	Slight
Specific Gravity:	1.10 at 80° F
Boiling Point:	More than 300° F
Volatile Organic Compound (EPA Method 24)	10.0%
Evaporation Rate (Ether = 1)	Not available
ph.:	Does not apply
Appearance:	Amber Liquid
Odor:	Mild

IV. SPILL OR LEAK AND DISPOSAL PROCEDURES

Steps to be taken in case

Of spill or leak: Soak up with an inert absorbent.Store in partly Filled, closed container until disposal.

Recommended methods

Of disposal: Incinerate following EPA and local regulations.

V. STORAGE AND HANDLING PROCEDURES

Storage: Store below 80 ° F to achieve maximum shelf life.

Handling: Avoid prologed skin contact. Keep away from eyes.

VI. REACTIVITY DATA

Stability: Stable
Hazardous Polymerization: Will Not Occur
Hazardous Decomposition
Products (non-thermal): None
Incompatibility: None

VII. PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Rubber or plastic gloves.
Ventilation: Does not apply.

VIII. EMERGENCY TREATMENT PROCEDURES

Ingestion: Do not induce vomiting. Keep individual calm.
Obtain medical attention.
Inhalation: Does not apply
Skin Contact: Flush with water
Eye Contact: Flush at least 15 minutes with water. Obtain medical attention.

IX. HEALTH HAZARD DATA

Toxicity: Eye irritant.
Estimated oral LD50 more than 5000mg/kg.
Estimated dermal LD50 more than 2000mg/kg.
Primary Routes of Entry: None known
Signs and Symptoms of Exposure: May cause dermatitis on prolonged contact in sensitive individuals.
Existing Conditions